



Easy Network, Trustable

# 150Mbps Wireless N Router

## WF2411PS



### Features:

- > Excellent wireless N speed up to 150Mbps, ideal for file sharing, online gaming and Internet calling
- > Passive WAN connection to power up the outdoor CPE (for some ISP's devices), Maximum PoE power up to 10W
- > Multiple wireless modes- AP, Repeater, AP+WDS, WDS, Client
- > Multi-SSID providing up to 3 additional separate networks for guests and friends
- > Easy wireless security setup at a push of the WPS button
- > Intelligent bandwidth control to manage the bandwidth usage for each computer reasonably
- > Internet Access Control- IP filtering, MAC Filtering, Domain Filtering based on time
- > 5dBi external antenna ensuring better performance than internal antenna products
- > Quick setup, with built-in multilingual management page

### What it does :

The netis WF2411PS 150Mbps Wireless N Router is a combined wired and wireless device for SOHO network applications. It's compatible with 802.11b/g/n devices and provides the wireless transfer speed up to 150Mbps, offering a better performance on web surfing, emailing, and file sharing. With PoE WAN Port, WF2411PS can supply maximum 10W power to your outdoor CPE device, enabling the data transmission from outdoor devices to router by cable connection.

## Specification:

Wireless	
Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Signal Rate	Up to 150Mbps
Frequency Range	2.4-2.4835GHz
Transmit Power	20 dBm (MAX)
Data Transfer Rates	802.11n: 40MHz(150Mbps, 135Mbps, 120Mbps, 90Mbps, 60Mbps, 45Mbps, 30Mbps, 15Mbps) 20MHz (72Mbps, 65Mbps, 57Mbps, 43Mbps, 28Mbps, 21Mbps, 14Mbps, 7Mbps) 801.11g: (54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps) 802.11b: (11Mbps, 9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps)
Wireless Modes	AP, Repeater, AP+WDS, WDS, Client, Multiple SSID
Wireless Security	64/128-bit WEP    WPA-PSK/WPA2-PSK (TKIP/AES)    SSID Broadcast Enable/Disable    Wireless MAC Filtering
Hardware	
Standard	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX
Interface	1 * 10/100Mbps Auto MDI/MDIX RJ45 WAN port, Passive PoE Supported(PSE Device) 4 * 10/100Mbps Auto MDI/MDIX RJ45 LAN port
LED Indicator	SYS, WPS, WAN, LAN1-LAN4
Button	WPS, Default
Antenna	1 * External 5dBi Fixed Antenna
Power Supply	DC 18V/750mA(Output)
Software	
WAN Type	DHCP(Dynamic IP), Static IP, PPPoE, L2TP, PPTP, Dual Access, WISP
Port Forwarding	Virtual Servers, Port Triggering, UPnP, DMZ, FTP Private Port
QoS	WMM, Bandwidth Control
Access Control	IP/MAC/Domain Filtering
VPN Pass-through	PPTP, L2TP, IPSEC
Others	DDNS, Static Routing, WOL, Backup & Restore, Firmware Upgrade
Others	
Certification	FCC, CE
Environment	Operating Temperature: 0°C~40°C Storage Temperature: -40°C~70°C Operating Humidity: 10%~90% non-condensing    Storage Humidity: 5%~90% non-condensing
Package	1 *WF2411PS 1 *18V/750mA Power Adapter 1 *Quick Installation Guide

## Topological Graph:

